



Sample image

C80-6

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Ring type terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i

| Voltage (V) | AC / DC |
|-------------|---------|
| 690 | AC |

Rated impulse withstand voltage U_{imp}

| Voltage (kV) | Overtension category | Pollution degree | Supply system | Function |
|--------------|----------------------|------------------|--|------------------------------|
| 6 | III | 3 | Valid for lines with grounded common neutral termination | Switch / Switch disconnecter |

Rated uninterrupted current I_u /Ith

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | additional requirements |
|-------------|--------------------------|-----------------------|--|
| 115 | 55 | 60 | Ambient temperature +55°C during 24 hours with peaks up to +60°C |

Rated operational current I_e

| Utilization category | Voltage (V) | Current (A) |
|----------------------|-------------|-------------|
| AC-13 | 230 | 50 |
| AC-20A | 690 | 115 |
| AC-21A | 20 - 690 | 100 |
| AC-22A | 220 - 500 | 100 |
| AC-22A | 660 - 690 | 100 |

Rated operational power

| Utilization category | Voltage (V) | No. of phases | No. of poles | Power (kW) |
|----------------------|-------------|---------------|--------------|------------|
| AC-2 | 220 - 240 | 3 | 3 | 30 |
| AC-2 | 380 - 440 | 3 | 3 | 45 |
| AC-2 | 500 - 500 | 3 | 3 | 55 |
| AC-2 | 660 - 690 | 3 | 3 | 55 |
| AC-3 | 220 - 240 | 3 | 3 | 15 |
| AC-3 | 380 - 440 | 3 | 3 | 30 |
| AC-3 | 500 - 500 | 3 | 3 | 30 |
| AC-3 | 660 - 690 | 3 | 3 | 30 |
| AC-3 | 110 - 120 | 1 | 2 | 3,70 |
| AC-3 | 220 - 240 | 1 | 2 | 7,50 |
| AC-3 | 380 - 440 | 1 | 2 | 13 |
| AC-4 | 220 - 240 | 3 | 3 | 6 |
| AC-4 | 380 - 440 | 3 | 3 | 11 |
| AC-4 | 500 - 500 | 3 | 3 | 11 |
| AC-4 | 660 - 690 | 3 | 3 | 11 |
| AC-4 | 110 - 120 | 1 | 2 | 1,50 |
| AC-4 | 220 - 240 | 1 | 2 | 3 |
| AC-4 | 380 - 440 | 1 | 2 | 5,50 |
| AC-23A | 220 - 240 | 3 | 3 | 30 |
| AC-23A | 380 - 440 | 3 | 3 | 45 |
| AC-23A | 500 - 500 | 3 | 3 | 55 |
| AC-23A | 660 - 690 | 3 | 3 | 45 |
| AC-23A | 110 - 120 | 1 | 2 | 5,50 |
| AC-23A | 220 - 240 | 1 | 2 | 15 |
| AC-23A | 380 - 440 | 1 | 2 | 22 |

Max. Fuse rating IEC

| Fuse characteristic | No. of Fuses | Current (A) |
|---------------------|--------------|-------------|
| gG | 1 | 125 |

UL60947-4-1, UL508

Rated insulation voltage U_i

| Voltage (V) | AC / DC |
|-------------|---------|
| 600 | AC |

| Rated thermal current | | | |
|-----------------------|-------------|--------------------------|-----------------|
| | Current (A) | Ambient temperature (°C) | Additional Text |
| | 100 | 0 - 40 | -- |

GENERAL TECHNICAL INFORMATION

| Tightening torque of screws | | |
|-----------------------------|------------------------|---------------------------|
| | tightening torque (Nm) | tightening torque (lb-in) |
| | 4 | 35 |

| Rated short-time withstand current Icw | | |
|--|----------|-------------|
| | Time (s) | Current (A) |
| | 1 | 1300 |

| Approbations | |
|---------------|---------|
| Specification | Marking |

EAC 

CE marking 

UK Directives
IEC 60947-3; EN 60947-3; VDE 0660 Teil107 

UL 60947-4-1; CSA C22.2 No. 60947-4-1 

GB/T14048.3 

| Power loss per pole | |
|---------------------|-----------|
| | Power (W) |
| | 5,80 |

| Conditions during transport and storing | | |
|---|--------------------------|--|
| Minimum temperature (°C) | Maximum temperature (°C) | additional requirements |
| -40 | 85 | In case of temperatures below -5°C no shock load permissible |

| Shock / Vibration | |
|-------------------------|--------------------------------------|
| Type of oscillation | Values |
| Resistance to shock | min. 5g, 30ms |
| Resistance to vibration | IEC 61373 (1999) Category 1, Class B |

General Information

- Text**
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
 - After wiring, ALL terminal screws must be tightened to the specified torque values.
 - The protection class of the selected mounting type may vary if optional extras are used.
 - Do not lubricate or treat contacts.
 - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
 - After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

| Operating temperature | | |
|-----------------------|-----------------------|-----------------------|
| | Min. Temperature [°C] | Max. Temperature [°C] |
| | -25 | 60 |