



Sample image

## KG100

Type Size: S1

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

**Rated insulation voltage  $U_i$** 

| Voltage (V) | AC / DC |
|-------------|---------|
| 690         | AC      |

**Rated impulse withstand voltage  $U_{imp}$** 

| Voltage (kV) | Overvoltage category | Pollution degree | Supply system  | Function                     |
|--------------|----------------------|------------------|--|------------------------------|
| 6            | III                  | 3                | Valid for lines with grounded common neutral termination | Switch / Switch disconnecter |

**Rated uninterrupted current  $I_u$ /I<sub>th</sub>**

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | additional requirements  |
|-------------|--------------------------|-----------------------|--|
| 100         | 50                       | 55                    | Ambient temperature +50°C during 24 hours with peaks up to +55°C |

**Conventional enclosed thermal current  $I_{the}$** 

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | Additional requirements  | No. of stages (from - to) | Mounting | Mounting size |
|-------------|--------------------------|-----------------------|--|---------------------------|----------|---------------|
| 100         | 35                       | 40                    | Ambient temperature +35°C during 24 hours with peaks up to +40°C | --                        | --       | --            |

**Rated operational current  $I_e$** 

| Utilization category | Voltage (V) | Current (A) |
|----------------------|-------------|-------------|
| AC-32A               | 20 - 400    | 100         |
| AC-20A               | 690         | 100         |
| AC-21A               | 20 - 690    | 100         |
| AC-22A               | 220 - 500   | 100         |
| AC-22A               | 660 - 690   | 85          |

**Rated operational power**

| Utilization category | Voltage (V) | No. of phases | No. of poles | Power (kW) |
|----------------------|-------------|---------------|--------------|------------|
| AC-3                 | 220 - 240   | 3             | 3            | 18,50      |
| AC-3                 | 380 - 440   | 3             | 3            | 30         |
| AC-3                 | 500 - 500   | 3             | 3            | 37         |
| AC-3                 | 660 - 690   | 3             | 3            | 22         |
| AC-23A               | 220 - 240   | 3             | 3            | 22         |
| AC-23A               | 380 - 440   | 3             | 3            | 37         |
| AC-23A               | 500 - 500   | 3             | 3            | 45         |
| AC-23A               | 660 - 690   | 3             | 3            | 30         |

**Max. Fuse rating IEC**

| Fuse characteristic | No. of Fuses | Current (A) |
|---------------------|--------------|-------------|
| gG                  | 1            | 100         |

### UL60947-4-1, UL508

**Rated insulation voltage  $U_i$** 

| Voltage (V) | AC / DC |
|-------------|---------|
| 600         | AC      |

**Rated thermal current**

| Current (A) | Ambient temperature (°C) | Additional Text |
|-------------|--------------------------|-----------------|
| 100         | 0 - 40                   | --              |

**General Information**
**Text**

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

- When intended for use as a motor disconnecter the device shall be provided with a method of being locked in the OFF-position.

### CSA

**Rated insulation voltage  $U_i$** 

| Voltage (V) | AC / DC |
|-------------|---------|
| 600         | AC      |

| Rated thermal current |                          |                 |  |
|-----------------------|--------------------------|-----------------|--|
| Current (A)           | Ambient temperature (°C) | Additional Text |  |
| 100                   | 0 - 40                   | -               |  |

**GENERAL TECHNICAL INFORMATION**

| Tightening torque of screws |                           |
|-----------------------------|---------------------------|
| tightening torque (Nm)      | tightening torque (lb-in) |
| 3                           | 27                        |

| Rated short-time withstand current Icw |             |
|--|-------------|
| Time (s)                               | Current (A) |
| 1                                      | 1850        |

| Size of conductor                                 |                   |                               |   |                      |
|---|-------------------|-------------------------------|---|----------------------|
| composition of conductor                          | Min. / Max. value | No. of conductor per terminal | Cross section (mm <sup>2</sup> ) or (AWG/kcmil) | Material of the wire |
| Solid wire  | Min.              | 1                             | 2.5mm <sup>2</sup>                              | Copper               |
| Flexible wire                                     | Min.              | 1                             | 4mm <sup>2</sup>                                | Copper               |
| Flexible wire                                     | Max.              | 1                             | 35mm <sup>2</sup>                               | Copper               |
| Flexible wire                                     | Max.              | 1                             | AWG 2   | Copper               |
| Single-core or stranded wire                      | Max.              | 1                             | AWG 1/0   | Copper               |
| Single-core or stranded wire                      | Max.              | 1                             | 50mm <sup>2</sup>                               | Copper               |
| Flexible wire with sleeve                         | Max.              | 1                             | 35mm <sup>2</sup>                               | Copper               |
| Flexible wire with ferrule according to DIN 46228 | Min.              | 1                             | 2.5mm <sup>2</sup>                              | Copper               |

| Approbations  |         |
|---------------|---------|
| Specification | Marking |

EAC



CE marking



UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

**IEC 60947-3**  
**EN 60947-3**

IEC 60947-6-1

**IEC 60947-6-1**  
**EN 60947-6-1**

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Russian Maritime Register of Shipping



| Power loss per pole |  |
|---------------------|--|
| Power (W)           |  |
| 2,40                |  |

| Conditions during transport and storing |                          |  |
|---|--------------------------|--|
| Minimum temperature (°C)                | Maximum temperature (°C) | additional requirements                                      |
| -40                                     | 85                       | In case of temperatures below -5°C no shock load permissible |

| Shock / Vibration       |                         |
|-------------------------|-------------------------|
| Type of oscillation     | Values                  |
| Resistance to vibration | Min. 4g, 2-100Hz, 1,6mm |
| Resistance to shock     | min. 6g, 6ms            |

| General Information |  |
|---------------------|--|
| Text                |  |

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.
- EMC Note: This device is suitable for use in environment A and B.
- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.

**General Information***Text*

- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

**Operating temperature***Min. Temperature [°C]*

-5

*Max. Temperature [°C]*

55