



Sample image

# KG41

**Type Size: S0**
**Classification Contact: Rigid contact bridge**
**Classification Contact Mat: Silver**
**Classification Terminal: Screw terminal**

## IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

**Rated insulation voltage  $U_i$** 

Voltage (V)	AC / DC
690	AC

**Rated impulse withstand voltage  $U_{imp}$** 

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

**Rated uninterrupted current  $I_u$ /I<sub>th</sub>**

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
40	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

**Conventional enclosed thermal current  $I_{the}$** 

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
40	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

**Rated operational current  $I_e$** 

Utilization category	Voltage (V)	Current (A)
AC-32A	20 - 400	40
AC-20A	690	40
AC-21A	20 - 690	40
AC-22A	220 - 500	40
AC-22A	660 - 690	40

**Rated operational power**

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	7,50
AC-3	380 - 440	3	3	11
AC-3	500 - 500	3	3	15
AC-3	660 - 690	3	3	11
AC-23A	220 - 240	3	3	7,50
AC-23A	380 - 440	3	3	15
AC-23A	500 - 500	3	3	18,50
AC-23A	660 - 690	3	3	15

**Max. Fuse rating IEC**

Fuse characteristic	No. of Fuses	Current (A)
gG	1	50

## UL60947-4-1, UL508

**Rated insulation voltage  $U_i$** 

Voltage (V)	AC / DC
600	AC

**Rated thermal current**

Current (A)	Ambient temperature (°C)	Additional Text
42	0 - 40	--

**General Information**
**Text**

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.
- When intended for use as a motor disconnecter the device shall be provided with a method of being locked in the OFF-position.

## CSA

**Rated insulation voltage  $U_i$** 

Voltage (V)	AC / DC
600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	40	0 - 40	-

**GENERAL TECHNICAL INFORMATION**

Tightening torque of screws	
	tightening torque (Nm)
	1,80

Rated short-time withstand current low	
	Time (s)
	1

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm <sup>2</sup> ) or (AWG/kcmil)	Material of the wire
Solid wire	Min.	2	0.75mm <sup>2</sup>	Copper
Solid wire	Min.	1	1.5mm <sup>2</sup>	Copper
Flexible wire	Max.	1	AWG 6	Copper
Flexible wire	Min.	1	2.5mm <sup>2</sup>	Copper
Flexible wire	Max.	1	10mm <sup>2</sup>	Copper
Flexible wire	Min.	2	1.5mm <sup>2</sup>	Copper
Single-core or stranded wire	Max.	1	AWG 6	Copper
Single-core or stranded wire	Max.	1	16mm <sup>2</sup>	Copper
Flexible wire with sleeve	Max.	1	10mm <sup>2</sup>	Copper
Flexible wire with ferrule according to DIN 46228	Min.	2	0.75mm <sup>2</sup>	Copper
Flexible wire with ferrule according to DIN 46228	Min.	1	1.5mm <sup>2</sup>	Copper

Approbations	
Specification	Marking

EAC



CE marking



UK Directives

Lloyd's Register EMEA



IEC 60947-3; EN 60947-3; VDE 0660 Teil107

**IEC 60947-3**  
**EN 60947-3**

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Russian Maritime Register of Shipping



Power loss per pole	
	Power (W)
	1

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

Shock / Vibration	
Type of oscillation	Values
Resistance to vibration	Min. 4g, 2-100Hz, 1,6mm
Resistance to shock	min. 6g, 6ms

General Information	
Text	

- Use only copper wires with or without tinned/silver-plated individual wires. Soldering the end of the wire before wiring is not allowed.

- EMC Note: This device is suitable for use in environment A and B.

- Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.

**General Information***Text*

- After wiring, ALL terminal screws must be tightened to the specified torque values.
- The protection class of the selected mounting type may vary if optional extras are used.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

**Operating temperature***Min. Temperature [°C]*

-5

*Max. Temperature [°C]*

55